

## Description

### Terminal MC55i with Quad-Band - the compact terminal for low price!

- Quad-band GSM/GPRS
- Data, SMS
- GSM Antenna
- External power supply
- RS232 connection
- Plug-n-Play

Low price, small size device with external power supply and GSM antenna. Perfect solution to connect your PC or external device to GSM/GPRS network via one from two RS232 ports\*. Device supports GPRS Class 10, which warrants higher speed and more stable data transmission. Easy installation makes device user friendly.

\* option (standard one RS232 port)



## Description

Application	Quad-Band GSM terminal
Frequency	850/900/1800/1900 Mhz
GPRS parameters	GPRS multi-slot class 10
GSM parameters	AT Hayes GSM 07.05 and GSM 07.07
External power supply:	9-24 V DC
Dimension	75 x 55 x 25 mm
Weight	162 g
Temperature range	-20 °C to + 55 °C
Interfaces	SMA antenna connection
	SIM card interface 3 V, 1.8 V
	RS232 port (two in option)

Basic features GPRS	Data downlink transfer: max 85.6 kbps
	Data uplink transfer: max. 42.8 kbps
Specification for fax	Group 3, Class 2 and Class 1
Specification for SMS	Point-to-point MO and MT
	SMS cell broadcast Text and PDU mode
Specifications for data (GPRS)	Multislot class 10
	Full PBCCH support
	Mobile station class B
	Coding scheme 1-4
Order no.	MC55i terminal